

greasing equipment - dispensing guns

booster gun

B2



Features

- suitable for air powered greasing applications
- supplied as a standard gun on the P3, P6 and P8 complete grease pumps
- a couple of simple presses of the trigger will double output pressure
- supplied with 360° ZSB Swivel
- 5 year warranty
- 10 year parts availability

Specifications

- **wetted components:**
mild steel and nitrile rubber
- **max. operating pressure:**
69 000 kPa (10 000 psi, 690 bar)
- **swivel inlet:**
1/4" NPT (F)

Accessories

- PF9 Flexible Extension
- PF17 Flexible Extension

pressurite gun

KR



Features

- suitable for manual powered greasing applications
- supplied with the K3 Super-Lube® and K6 Mini-Lube®
- can deliver grease at either high volume or high pressure
- suitable for greases up to and including NLGI No.2
- 360° swivel to prevent hose kinking
- 5 year warranty
- 10 year parts availability

Specifications

- **wetted components:**
aluminium, steel and nitrile rubber
- **gun pressure:**
up to 69 000 kPa (10 000 psi, 690 bar)
- **output:**
approx. 1.25 g on the high volume switch and approx 0.45 g on the high pressure switch (to clear a blocked or seized nipple)

Accessories

- KF9 Flexible Extension/KDF13 Flexible Extension
- KZD Needlenose Coupler/KZHY Hyperdermic Needlepoint Coupler