

## greasing equipment - air operated

# maxi-lube®

### P6

The P6 Maxi-Lube® is a 50:1 ratio pump offering all the same features as the P3, yet has models available to suit grease containers from 50 kg (110lbs) to 55 kg (120lbs).

#### Features

- suitable for underground coal mine use
- non-corroding air motor which operates quietly
- complete unit supplied with pump lid, rubber edged follower plate, 4 m (13 ft) x 6 mm (1/4") ID SAE 100 R2 delivery hose, and B2 Booster Gun with 360° high pressure ZSB swivel (all components are available separately)
- handles up to and including NLGI No.2 greases
- no requirement for air line lubricator
- optional trolley available (TR6) for a portable system
- 5 year warranty
- 10 year parts availability

#### Specifications

- **wetted components:**  
zinc and hard chrome plated carbon steel, brass, and nitrile and polyurethane rubber
- **output:**  
approx. 460 g of NLGI No.2 grease per min.
- **max. air pressure:**  
1 030 kPa (150 psi, 10.3 bar)
- **min. air pressure:**  
400 kPa (60 psi, 4 bar)
- min. compressor size:  
0.08 m<sup>3</sup>/min (3 cfm)
- **air inlet:**  
1/4" NPT (F)
- **pump ratio:**  
50:1 (grease pressure is 50 times air pressure)
- **B2 gun pressure:**  
up to 69 000 kPa (10 000 psi, 690 bar)
- **hose thread:**  
1/4" NPT (M)

#### Accessories

- TR6 Trolley
- PDF13 Push On Extension
- PDF21 Push On Extension
- TA-4K Pressure Regulator Kit
- KZDXL Straight Needlepoint Coupler
- KRV Pressure Release Valve



TR6 Trolley

