

greasing equipment - hand operated

mini-lube®

K6

The K6 Mini-Lube® is a portable, manual greasing system designed for use both in workshop environments and for on site applications. Macnaught produces models to suit pail sizes from 2.5 kg (5 lbs) to 5 kg (11 lbs) with depths of 146 mm to 225 mm.

Features

- includes pump unit, lid, rubber edged follower, 1.5 m (5 ft) x 1/2" ID delivery hose, and the high pressure, high volume KR grease gun (all components also available separately)
- K6-24 contains the above items plus a 2.5 kg (5 lbs) refillable container (KT5), while the K6-67 contains the above items plus a 5 kg (11 lbs) refillable container (KT6)
- spring loaded pump system provides 30 shots of grease
- suitable for greases up to and including NLGI No.2
- 360° swivel to prevent hose kinking
- fully sealed to prevent contamination
- 5 year warranty
- 10 year parts availability

Specifications

- **wetted components:**
aluminium, steel, brass and nitrile rubber
- **gun pressure (on high pressure):**
up to 69 000 kPa (10 000 psi, 690 bar)
- **output:**
approx. 1.25 g on the high volume switch
approx. 0.45 g on the high pressure switch
(to clear a blocked or seized nipple)

Accessories

- KT5 (2.5 kg)/KT6 (5 kg) Grease Container
- KZD Needlenose Coupler
- KZHY Hyperdermic Needlepoint coupler
- KFR Rigid/Flexible Extension
- KDF13 Flexible Extension
- KSR Standard Buttonhead Coupler



KT5 (2.5 kg)/KT6 (5 kg) Grease Container

