

hose reels - retracta

retracta® auto rewind hose reels

Retracta® is the robust market leader in rewind hose reel systems. Retracta® is the answer to storage and safety problems, and the wide range of models allows the reel to be used in any industry work environment.

Features

- superior positive latching mechanism allows the reel to be mounted in any position
- weather resistant, high impact UV stabilised polypropylene
- safe storage system that keeps hoses off the floor
- versatile – average weight with hose is 12 kg
- low rewind tension allows for easy hose “pull out”
- full stainless steel mouth for improved hose and reel service life
- lockable wall or overhead mounting bracket BU100 is supplied with every hose reel purchase and allows for hose reel rotation through 180°
- optional BB100 bench or floor mounting bracket is available separately
- an ability to have colour coded reels to suit any application or fit within an individual corporate look (conditions apply)
- fully repairable
- 5 year warranty
- guaranteed availability of spare parts for 10 years

Accessories

- BB100 Retracta Branch Bracket

Model	Description	Hose ID	Hose Length	Working Pressure	Hose Material	Reel Colour	Hose Colour	Max Working Temp.	Reel Inlet (BSP/NPT)	Hose Outlet (BSP/NPT)	Weight	Max. Viscosity
AB100	air breathing	10 mm	17 m	1 700 kPa (250 psi)	reinforced PVC	blue	yellow	60° C	3/8"	1/4"	10 kg	n/a
AR100	compressed air	10 mm	20 m	1 700 kPa (250 psi)	reinforced PVC	red	red	60° C	3/8"	1/4"	10 kg	n/a
AR200	compressed air	12.5 mm	15 m	1 700 kPa (250 psi)	reinforced PVC	red	yellow	60° C	3/8"	3/8"	10 kg	n/a
AW100	compressed air/water	10 mm	20 m	1 700 kPa (250 psi)	reinforced PVC	blue	blue	60° C	3/8"	1/4"	10 kg	n/a
AW150	compressed air/water	10 mm	15 m	1 700 kPa (250 psi)	reinforced PVC	blue	blue	60° C	3/8"	1/4"	10 kg	n/a
AW200	compressed air/water	12.5 mm	15 m	1 700 kPa (250 psi)	reinforced PVC	blue	blue	60° C	3/8"	3/8"	10 kg	n/a
CW100	cold wash	12.5 mm	15 m	1 000 kPa (150 psi)	reinforced PVC	blue	white	60° C	3/8"	hose nozzle	10 kg	n/a
DR100	garden water	12.5 mm	18 m	860 kPa (125 psi)	reinforced PVC	green	green	60° C	3/8"	hose nozzle	10 kg	n/a
FG100	food gas/CO ²	6 mm	20 m	1 700 kPa (250 psi)	NTP	red	clear	60° C	3/8"	1/4"	10 kg	n/a
FR300	foam	16 mm	10 m	1 000 kPa (150 psi)	reinforced PVC	white	white	60° C	3/8"	N/A	10 kg	n/a
GR100	grease	6 mm	10 m	34 500 kPa (5000 psi)	reinforced rubber (SAE 100R2)	black	black	n/a	1/4"	1/4"	13 kg	n/a
HW100	hot water	12.5 mm	12 m	1 400 kPa (200 psi)	reinforced rubber	red	red	90° C	3/8"	3/8"	10 kg	n/a
HWP100*	high pressure hot water	10 mm	12 m	20 700 kPa (3000 psi)	reinforced rubber (SAE 100 R2AT)	red	black	95° C	3/8"	3/8"	12 kg	n/a
OA100**	oxy/acetylene	5 mm	15 m	1 400 kPa (200 psi)	reinforced rubber (AS 1335)	blue	red/blue**	n/a	5/8" UNF	5/8" UNF	13 kg	n/a
OLPG100**	oxy/LPG gas	5 mm	15 m	1 400 kPa (200 psi)	reinforced rubber (AS 1335)	black	orange/blue**	n/a	5/8" UNF	5/8" UNF	13 kg	n/a
OLP100	low pressure oil	12.5 mm	10 m	2 800 kPa (400 psi)	reinforced rubber (SAE 100R6)	blue	black	95° C	3/8"	1/2"	10 kg	SAE 140
OMP100	medium pressure oil	10 mm	10 m	6 900 kPa (1000 psi)	reinforced rubber (SAE 100R1)	blue	black	n/a	3/8"	1/2"	13 kg	SAE 140
FW100	potable water	12.5 mm	15 m	1 000 kPa (150 psi)	reinforced LDPE	blue	blue	60° C	3/8"	3/8"	10 kg	n/a
WP100	weedicide/pesticide	10 mm	16 m	1 700 kPa (250 psi)	reinforced PVC	red	red	60° C	3/8"	1/4"	10 kg	n/a

* HWP100 is not suitable for use with steam

** Specifications for OA100/OLPG100 are for Australian models only.



BU100

BB100

